

Material Safety Data Sheet

Page: 1 of 4

Date of Issue: January 2014

Otech 518 – Bitumen Extender Oil

COMPANY DETAILS

Company Name Oil Technology Australia

Address Cnr Boundary Road & Potassium Street

NARANGBA QLD 4504 AUSTRALIA

Emergency Tel. 0417 217 332 **Product and MSDS Info:** 07 3203 2833

IDENTIFICATION

Product Name Solvent Neutral Base Oil **Chemical Name** Petroleum Hydrocarbons

Physical Data

Appearance Liquid Colour Amber **Boiling point** > 316°C **Melting point** N/A

Flash point (PMCC) > 210°C (ASTM D-93)

Flammability N/E **Auto Flammability** N/E

Solubility in Water Negligible

Other Properties

pН N/A **Explosive Properties** N/A **Oxidizing Properties** N/A

Vapour Pressure < 0.1 (mmHg @ 20°C)

Vapour Density > 2.0**Evaporation Rate** N/E

Relative Density 0.87 (@15°C)

Partition Coefficient > 3.5

45 cSt (@ 40°C typical) Viscosity

7.0 cSt (@ 100°C typical)

Pour Point < -9°C **Freezing Point** N/E

N/A=NOT APPLICABLE N/E=NOT ESTABLISHED

Page: 2 of 4

Date of Issue: January 2014

Product: Otech 518 Bitumen Extender Oil

		Supplier: Oil	Technology Australia
Ingredients			
Ingredients	Name Solvent Treated Heavy Paraffinic Distillate	Proportion 100 %	CAS 64742-65-0
Information on Composition	Chemical Family: Petroleum Hydrocarbon		
Ingredients Considered Hazardous to Health	This product is not formulated to contain ingredients which have exposure limits established by U.S. agencies. It is not hazardous to health as defined by the European Union Dangerous Substances/Preparations Directives.		
	HEALTH HAZARD INFORMA	TION	
	Health Effects		
Acute – Swallowed	If more than several mouthfuls are nausea and diarrhea may occur.	swallowed, abdom	inal discomfort,
Acute – Eye	Not expected to cause eye irritation following short-term exposure.		
Acute – Skin	Expected to cause no more than minor skin irritation.		
Acute - Inhalation	Harmful concentrations of mists and/or vapors are unlikely to be		

Chronic	The base oil component(s) are not expected to be carcinogenic based on
	IARC criteria. This product has not been tested as a whole for chronic

use, or misuse of this product.

IARC criteria. This product has not been tested as a whole for chronic

encountered through any customary or reasonably foreseeable handling,

health effects.

First Aid **Swallowed** No specific first aid measures are required because this material is not

expected to be harmful if swallowed. Do not induce vomiting. As a precaution, give the person a glass of water or milk to drink and get medical advice. Never give anything by mouth to an unconscious person.

Eye Flush eyes immediately with fresh water for several minutes while holding

the eyelids open.

Skin Wash skin thoroughly with soap and water.

Inhaled If respiratory irritation or any signs or symptoms as described in this

MSDS occur, move the person to fresh air. If any of these effects continue,

see a doctor.

Advice to Doctor N/A

Page: 3 of 4
Date of Issue: January 2014
Product: Otech 518 Bitumen Extender Oil
Supplier: Oil Technology Australia

	Supplier on recimology russium	
	PRECAUTIONS FOR USE	
Exposure Limits	This product does not contain any components which have recognized exposure limits. However, an exposure limit of 5.00 mg/m3 is suggested for oil mist.	
Eng. Controls	Use in well ventilated area or with local exhaust ventilation. Vapour heavier than air – prevent concentration in hollows or sumps. Do not enteronfined spaces where vapour may have collected.	
	Personal Protection	
Eye Protection	Safety glasses	
Clothing	Overalls, safety shoes and gloves.	
Work/Hygienic Practices	Avoid skin and eye contact and inhalation of vapours. Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.	
	Flammability	
Fire Hazards	See Safe Handling Information.	
	SAFE HANDLING INFORMATION	
	Storage and Transport	
Transport	Not classified as dangerous by the criteria of the Australian Dangerous Goods Code (ADG) for transport by road or rail. UN Number: N/A Dangerous Good Class: N/A Proper Shipping Name: N/A Hazchem Code (Aus/NZ): N/A	
Storage Regulations	Store in a well ventilated area. Store away from halogens, strong acids, alkalis, oxidizing agents and foodstuffs.	
	Spills and Disposal	
Spills & Disposal	Wear protective equipment to prevent skin and eye exposure and inhalation of vapours/mists. Work upwind or increase ventilation. Contain any spillage using absorbent soil, sand or any other inert material and prevent runoff to drains and waterways. Collect, seal and label drums for disposal. Wash down with detergent and excess water.	
Disposal	Refer to State Land Waste Management Authority. Normally suitable for incineration by approved agent.	

Page: 4 of 4

Date of Issue: January 2014

Product: Otech 518 Bitumen Extender Oil **Supplier:** Oil Technology Australia

	Fire/Explosion Hazard	
Fire/Explosion Hazard	Combustible liquid. May form flammable vapour mixes with air. Electrical requirements for work areas should be assessed according to AS 3000. On burning, will emit toxic fumes, including carbon monoxide (CO). Firefighters to wear self-contained breathing apparatus if risk of exposure to vapour or products of combustion.	
Extinguishing Media	Foam, dry agent (CO ₂ or dry chemical powder).	
	OTHER INFORMATION	
Toxicology	This product contains petroleum base oils which has been refined by processes including severe solvent extraction. These oils have not been listed in the U.S. National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as carcinogenic or probably carcinogenic to humans. Oral LD50 (Rat) >2000 mg kg ⁻¹ Dermal LD50 (Rabbit) >2000 mg kg ⁻¹	
Environmental Protection	Avoid contaminating waterways. Harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.	
	CONTACT POINT	
Contact	OTECH AUSTRALIA Cnr Boundary Rd & Potassium St Narangba QLD 4504 Telephone: (07) 3203 2833 Fax: (07) 3203 3700	

The information contained in this MSDS is as accurate as we can ascertain at the this time. However, as the information is gleaned from a number of third party sources. Otech Australia can make no warranty, guarantee or statement as to the reliability or completeness of the information. Otech Australia will not accept liability for any damages whatsoever arising from reliance on this information. It is the responsibility of the user to satisfy himself as to the suitability and completeness of such information for his own use.