

**CONTACT POINT**

Ray Georgey
Corporate Energy Australia
cnr Boundary Rd & Potassium St
NARANGBA QLD 4504
Ph: 07 3203 2833
Fax: 07 3203 3700

MATERIAL SAFETY DATA BULLETIN**DIAMIN TOL****HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA****PRODUCT INFORMATION**

UN No.:	2735	D.G. CLASS NO:	8	CAS NO:	7173-62-8
HAZCHEM:	3X	SUBRISK:	n/a	SUSDP:	None allocated
G.T. EPG:	8A1	SPEC. EPG:	None allocated	IMDG:	8109-2
PACKING GROUP:	II				

PRODUCT IDENTIFICATION

CORRECT SHIPPING NAME: Alkyl Amine N.O.S. (N-OLEYL PROPYLENE DIAMINE)
OTHER NAMES: None Allocated

TRADE NAMES:	MANUF.:	MANCODE:
DIAMIN TO-L	Quimikao	03705105
DIAMIN TO-L	Quimikao	00300262 (20 kg)

INGREDIENTS:		
CHEMICAL ENTITY:	CAS NO:	PROPORTION:
DIAMIN TO-L	7173-62-8	100 %

PHYSICAL DESCRIPTION / PROPERTIES:

APPEARANCE:	Oily yellow liquid with an ammonia smelling odour.
BOILING POINT:	> 250°C
VAPOR PRESSURE:	Not available
SPECIFIC GRAVITY (@ 25°C):	0.85
FLASH POINT:	> 140°C
FLAMMABILITY LIMITS:	None allocated
REL. VAPOR DENSITY:	(air = 1) : > 1.0
DECOMPOSITION TEMP.:	> 250°C
SOLUBILITY IN WATER:	Insoluble
USE:	Bitumen Adhesion Agent



CONTACT POINT

Ray Georgey
Corporate Energy Australia
cnr Boundary Rd & Potassium St
NARANGBA QLD 4504
Ph: 07 3203 2833
Fax: 07 3203 3700

MATERIAL SAFETY DATA BULLETIN
Diamin Tol

HEALTH HAZARD INFORMATION

ACUTE EFFECTS:

- SWALLOWED:** Results in severe damage to mucous membranes.
EYES: Causes severe irritation, burn and possible eye damage.
SKIN: Causes severe skin irritation or burn. Causes skin irritation, blistering and/or dermatitis.
INHALED: May cause symptoms of lack of oxygen, leading to collapse and possible death. Vapours, specially when heated, cause nose and throat irritation.
CHRONIC EFFECTS: None allocated.

FIRST AID

- SWALLOWED:** If victim is conscious, give at least 2 glasses of water to dilute or lightly acidified water with vinegar to neutralise. Do not induce vomiting, this is a caustic and corrosive compound. Obtain medical attention promptly.
EYES: Flush eyes immediately with 0.5 – 1.0% aqueous boric acid solution, lifting upper and lower lids occasionally and after this, wash with large amounts of water for at least 15 minutes. Obtain medical attention promptly.
SKIN: Remove all contaminated clothes. Wash affected body areas with 3% aqueous acetic acid solution and after this, wash with large amounts of water for at least 15 minutes. Obtain medical attention.
INHALED: Remove victim to fresh air and keep warm. Give oxygen or artificial respiration as needed. Obtain medical attention promptly.

FIRST AID FACILITIES: Standard first aid facilities.

ADVICE TO DOCTOR: Treat symptomatically.



CONTACT POINT

Ray Georgey
Corporate Energy Australia
cnr Boundary Rd & Potassium St
NARANGBA QLD 4504
Ph: 07 3203 2833
Fax: 07 3203 3700

MATERIAL SAFETY DATA BULLETIN
Diamin Tol

PRECAUTIONS FOR USE

EXPOSURE STANDARDS: None allocated.

ENGINEERING CONTROLS: None allocated.

PERSONAL PROTECTION:

EYES: Wear face shields and splash proof safety goggles.
SKIN: Wear appropriate clothing, butyl rubber or neoprene gloves and boots.
Wear full head protection.
RESPIRATORY: Equipment should prevent repeated or prolonged contact respiratory tract.
When airborne exposure limit and/or comfort levels may be exceeded use a SA1716 approved Type K respirator consistent with the airborne concentrations. When using organic chemical cartridges ensure that the cartridges are correct for the potential air contamination and are in good working order.

FLAMMABILITY: Combustible liquid.

ENVIRONMENT: None allocated.

SAFE HANDLING INFORMATION

STORAGE & TRANSPORT

STORAGE: Tanks, drums or containers : Carbon Steel, high density polyethylene, stainless steel, fibre glass (F.R.P.)
Storage Conditions: Containers away from sparks, open flame and strong oxidizing agents.

LOADING/UNLOADING TEMPERATURE: 30°C

